



## H05Z-K



### CONSTRUCTION

CONDUCTOR	Fine-Stranded Annealed Copper Conductor (IEC 60228-Class 5)
INSULATION	XL-HF

### PHYSICAL&ELECTRICAL CHARACTERISTICS

MAX. CONDUCTOR TEMPERATURE DURING SHORT CIRCUIT	250°C
NOMINAL VOLTAGE	300/500 V
TEST VOLTAGE	2000 V
OPERATING TEMPERATURE	-40°C ... +90°C
MINIMUM BENDING RADIUS	10 X D

### FIRE PERFORMANCE CHARACTERISTICS

FLAME RETARDANT	IEC 60332-1
NO FLAME PROPAGATION	IEC 60332-3-24
HALOGEN-FREE	IEC 60754-1, VDE 0482 P267-2-1, DIN EN50267-2-1
NO CORROSIVE GASES	IEC 60754-2, VDE 0482 P267-2-2, DIN EN 50267-2-2
LOW SMOKE EMISSION	IEC 61034-1/-2, VDE 0482 P268-1/-2, DIN EN 50268-1/-2



## H05Z-K



### OTHER CHARACTERISTICS

UV RESISTANCE	ISO 4892-2 / ISO 4892-3
WATER RESISTANCE	AD7
OIL RESISTANCE	ASTM NO: 2 (4 hours 70°C)
HYDROCARCON RESISTANCE	NF-M87-202 (Aliphatic Hydrocarbon)

### DIMENSIONS

Number of Core and Cross Section Area (mm <sup>2</sup> )	Approx. Overall Diameter (mm) (±5%)	Approx. Cable Weight (kg/km)	Max. Conductor Resistance DC at 20°C (Ohm/km)
1 x 185	23,60	1760	0,106