HSLHSH (SH)

CONSTRUCTION

CONDUCTOR	Fine-Stranded Annealed Copper Conductor (IEC 60288-Class 5)	
INSULATION	LSZH Compound	JZ-OZ-DIN 47100
BEDDING	LSZH Compound	
BRAID	Tinned Copper Wire Braid	70% Coverage
SHEATH	LSZH Compound	Black

PHYSICAL&ELECTRICAL CHARACTERISTICS

MAX. CONDUCTOR TEMPERATURE DURING SHORT CIRCUIT	250°C
NOMINAL VOLTAGE	600/1000 V
TEST VOLTAGE	3500 V
OPERATING TEMPERATURE	-40°C ... +70°C
MINUMUM BENDING RADIUS	12 X D

FIRE PERFORMANCE CHARACTERISTICS

FLAME RETARDANT	IEC 60332-1
NO FLAME PROPAGATION	IEC 60332-3-24
HALOGEN-FREE	IEC 60754-1, VDE 0482 P267-2-1, DIN EN50267-2-1
NO CORROSIVE GASES	IEC 60754-2, VDE 0482 P267-2-2, DIN EN 50267-2-2
LOW SMOKE EMISSION	IEC 61034-1/-2, VDE 0482 P268-1/-2, DIN EN 50268-1/-2

Osmangazi Mahallesi Mareşal Fevzi Çakmak Caddesi
No:19 Kıraç-Esenyurt / İSTANBUL
+90 (212) 689 49 00
info@demes.com.tr

HSLHSH (SH)

OTHER CHARACTERISTICS

UV RESISTANCE	ISO 4892-2 / ISO 4892-3
WATER RESISTANCE	AD7
OIL RESISTANCE	ASTM NO: 2 (4 hours 70°C)
HYDROCARCON RESISTANCE	NF-M87-202

DIMENSIONS

Number of Core and Cross Section Area (mm²)	Approx. Overall Diameter (mm) (±5%)	Approx. Cable Weight (kg/km)	Max. Conductor Resistance DC at 20°C (Ohm/km)
14 x 1,5	19,10	613	13,3

Osmangazi Mahallesi Mareşal Fevzi Çakmak Caddesi
No:19 Kıraç-Esenyurt / İSTANBUL
+90 (212) 689 49 00
info@demes.com.tr